

# DP-860

## Compact Size with Integrated HulaPoint II™

The small footprint DP-860 is built for versatility and convenience. It features 84-key functionality and an integrated HulaPoint II™, an upgraded pointing device that offers improved sensitivity and increased durability. Constructed with a sealed, industrial silicone keypad and designed to meet NEMA 4X specifications, the DP-860 is ideal for mobile applications and space saving. In addition, its integrated HulaPoint II™ pointing device eliminates the need for an external mouse.



### Technical Specifications

Certifications	NEMA 4X CE, UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 4 ft coiled (1.2m) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 7.5 oz +/- 1.06 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	KEYBOARD: 50mA@5V (from keyboard port) HULAPOINT: 35mA@5V (from mouse port) USB: 85mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE CABLE: 94 VO
Compatability	PS/2 KEYBOARD/HULPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (+4F to +140F)
Weight	2 lbs +/- 0.10 lbs (0.91 kg +/- .05 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	11.40" x 6.30" x 1.86" (w-h-d) 289.56mm x 160.02mm x 47.24mm
Model Numbers	

### Features and Benefits

- 12 Function Keys
- Built-In Mounting Holes
- Lightweight ABS Polycarbonate Case
- 84-Key Functionality
- Integrated HulaPoint II Pointing Device
- USB and PS/2 configurations available